

GSX-R 1000R

GSX-R 1000

Own The Racetrack



IMPORTED FROM JAPAN 



GSX-R1000R (GSX-R1000RZA)



Metallic Triton Blue / Metallic Mystic Silver (GUL)

GSX-R1000R (GSX-R1000RA)



Metallic Mat Black No.2 (4TX)

GSX-R1000 (GSX-R1000A)



Metallic Mat Black No.2 (YKV)

SPECIFICATIONS

Engine type	4-stroke, 4-cylinder, liquid-cooled, DOHC
Bore x stroke	76.0 mm x 55.1 mm
Displacement	999.8 cm ³
Compression ratio	13.2 : 1
Fuel system	Fuel injection
Starter system	Electric
Ignition system	Electronic ignition (transistorized)
Lubrication system	Wet sump
Transmission	6-speed constant mesh
Primary reduction ratio	1.652 (76/46)
Front suspension	Inverted telescopic, coil spring, oil damped
Rear suspension	Link type, coil spring, oil damped
Rake / trail	23°20' / 95 mm

Front brake	Disc, twin
Rear brake	Disc
Front tire size	120/70ZR17M/C (58W), tubeless
Rear tire size	190/55ZR17M/C (75W), tubeless
Overall length	2,075 mm
Overall width	705 mm
Overall height	1,145 mm
Wheelbase	1,420 mm
Ground clearance	130 mm
Seat height	825 mm
Curb mass	203kg
Fuel tank capacity	16L
Oil capacity (Overhaul)	4.1L




*GSX-R1000R Only



Ride by Wire Throttle Bodies



Full LCD instrument cluster



Suzuki Drive Mode Selector (SDMS) And Motion Track TCS (Traction Control System)



Bi-Directional Quick Shift System



Proven Showa Suspension



Improved Aerodynamics

IMPORTED FROM JAPAN



SUZUKI MALAYSIA SDN. BHD. 202001012115 (1368435-X)

(Sole Importer / Assembler / Distributor for Suzuki Motorcycles, Scooters, ATV, Spare Parts & Accessories)

No.12 & 14, Jalan Jurunilai U1/20, Seksyen U1, Hicom Glenmarie Industrial Park, 40150 Shah Alam, Selangor Darul Ehsan.

Tel: 603-5566 5688 Fax: 603-5566 5699

f suzukimalaysia | suzukimalaysiasb | suzukimalaysia1 | www.suzuki.com.my



* Specifications are subject to change without prior notice
** Pictures displayed are for illustration purposes only.
Actual product may vary.

