

KATANA



Feel the Edge

IMPORTED FROM JAPAN 





Sharp face with LED headlight and LED front position lights



Rear LED combination lights



Multi-function instrument cluster



Engine design - outline



Fully adjustable, inverted front forks



3-mode traction control system

SPECIFICATIONS

Engine type	4-stroke, 4-cylinder, liquid-cooled, DOHC
Bore x stroke	73.4 mm x 59.0 mm
Displacement	999 cm ³
Compression ratio	12.2 : 1
Fuel system	Fuel injection
Starter system	Electric
Ignition system	Electronic ignition (transistorized)
Lubrication system	Wet sump
Transmission	6-speed constant mesh
Front suspension	Inverted telescopic, coil spring, oil damped
Rear suspension	Link type, coil spring, oil damped
Rake / trail	25° / 100mm
Front brake	Disc, twin
Rear brake	Disc
Front tire size	120/70ZR17M/C (58W), tubeless
Rear tire size	190/50ZR17M/C (73W), tubeless
Overall length	2,130 mm
Overall width	835 mm
Overall height	1,110 mm
Wheelbase	1,460 mm
Ground clearance	140 mm
Seat height	825 mm
Curb mass	215kg
Fuel tank capacity	12 L

KATANA (GSX-S1000S)



Metallic Mystic Silver (YMD)



Glass Sparkle Black (YVB)



* Specifications are subject to change without prior notice
 ** Pictures displayed are for illustration purposes only.
 Actual product may vary.

IMPORTED FROM JAPAN 



SUZUKI MALAYSIA SDN. BHD. 202001012115 (1368435-X)

(Sole Importer / Assembler / Distributor for Suzuki Motorcycles, Scooters, ATV, Spare Parts & Accessories)

No.12 & 14, Jalan Jurunilai U1/20, Seksyen U1, Hicom Glenmarie Industrial Park, 40150 Shah Alam, Selangor Darul Ehsan.

Tel: 603-5566 5688 Fax: 603-5566 5699

 [suzukimalaysia](https://www.facebook.com/suzukimalaysia)  [suzukimalaysiasb](https://www.instagram.com/suzukimalaysiasb)  [suzukimalaysia1](https://twitter.com/suzukimalaysia1)  www.suzuki.com.my

