

SV650

V-Twin Fun And Excitement



IMPORTED FROM JAPAN 



SV650 (SV650A)



Pearl Brilliant White / Glass Sparkle Black (B1G)



Dual Spark 90° V-Twin



Dual Spark Technology



Low RPM Assist



SDTV Fuel injection



LED Tail & Stop Lights



Full LCD Instrument Panel



Brakes & ABS



Truss Pipe Frame

Specifications

Engine type	4-stroke, 90° V-Twin, liquid-cooled, DOHC
Bore x stroke	81.0 mm x 62.6 mm
Displacement	645 cm ³
Compression ratio	11.2 : 1
Fuel system	Fuel injection
Starter system	Electric
Ignition system	Electronic ignition (Transistorized)
Lubrication system	Wet sump

Transmission	6-speed constant mesh
Front suspension	Telescopic, coil spring, oil damped
Rear suspension	Link type, coil spring, oil damped, spring preload adjustable
Rake / trail	25° / 106 mm
Front brake	Disc, twin
Rear brake	Disc
Front tire size	120/70ZR17M/C (58W), tubeless
Rear tire size	160/60ZR17M/C (69W), tubeless

Overall length	2,140 mm
Overall width	760 mm
Overall height	1,090 mm
Wheelbase	1,445 mm
Ground clearance	135 mm
Seat height	785 mm
Curb mass	198 kg
Fuel tank capacity	14.5L
Oil capacity (Overhaul)	3.0L



IMPORTED FROM JAPAN

* Specifications are subject to change without prior notice

** Pictures displayed are for illustration purposes only.

Actual product may vary.



SUZUKI MALAYSIA SDN. BHD. 202001012115 (1368435-X)

(Sole Importer / Assembler / Distributor for Suzuki Motorcycles, Scooters, ATV, Spare Parts & Accessories)

No.12 & 14, Jalan Jurunilai U1/20, Seksyen U1, Hicom Glenmarie Industrial Park, 40150 Shah Alam, Selangor Darul Ehsan.

Tel: 603-5566 5688 Fax: 603-5566 5699

[suzukimalaysia](#) [suzukimalaysiasb](#) [suzukimalaysia1](#) [www.suzuki.com.my](#)

