







Bold, Breathtaking Style

SPECIFICATIONS Engine type

Bore x stroke

Displacement

Fuel system

Starter system

Ignition system

Transmission

Front suspension

Rear suspension

Rake / trail

Lubrication system

Compression ratio



Full LCD instrumentation

72.0 mm × 46.0 mm

749 cm³

12.3:1

Electric

Wet sump

25° / 100 mm

Fuel injection

4-stroke, 4-cylinder, liquid-cooled, DOHC


Electronic ignition (transistorized)

Link type, coil spring, oil damped

6-speed constant mesh



Greater power with fewer emissions - the best of both worlds



Solid arin tires Radial mounted four-piston onnosed front caliners

Front brake

Rear brake

Front tire size

Rear tire size

Overall length

Overall width

Overall height

Ground clearance

Fuel tank capacity

Oil capacity (Overhaul)

Wheelbase

Seat height

Curb mass

Mode	TC mode indicator	Sensitivity level	Good for
OFF	Y/F	31	
1		Low	Sport riding, good road conditions
2	YES.	Middle	City riding, regular road conditions
3	VLA	High	Wet or cold conditions

Three-mode traction control system

IMPORTED FROM JAPAN

120/70ZR17M/C (58W), tubeless

180/55ZR17M/C (73W), tubeless

Disc. twin

2,125 mm

785 mm

1,055 mm

1,455 mm

135 mm

820 mm

213kg

16L

3.9L

Disc



	5
P	
M.	

Metallic Triton Blue / Glass Sparkle Black (KEL)

GSX-S750 (GSX-S750ZA)

Metallic Oort Gray No.3 / Glass Sparkle Black (BD7)

















- * Specifications are subject to change without prior notice
- ** Pictures displayed are for illustration purposes only. Actual product may vary







Inverted telescopic, coil spring, oil damped







SUZUKI MALAYSIA SDN. BHD. 202001012115 (1368435-X)

(Sole Importer / Assembler / Distributor for Suzuki Motorcycles, Scooters, ATV, Spare Parts & Accessories)

No.12 & 14, Jalan Jurunilai U1/20, Seksyen U1, Hicom Glenmarie Industrial Park, 40150 Shah Alam, Selangor Darul Ehsan. Tel: 603-5566 5688 Fax: 603-5566 5699



suzukimalaysia



(ii) suzukimalaysiasb



suzukimalaysia1



www.suzuki.com.my





