

V-Stram 650XT

**ADVENTURE,
IN ALL DIRECTIONS**



IMPORTED FROM JAPAN 

 **SUZUKI**

 **AMI**

SPECIFICATIONS

Engine type	4-stroke, 90° V-Twin, liquid-cooled, DOHC
Bore x stroke	81.0 mm x 62.6 mm
Displacement	645 cm ³
Compression ratio	11.2 : 1
Fuel system	Fuel injection
Starter system	Electric
Ignition system	Electronic ignition
Lubrication system	Wet sump
Transmission	6-speed constant mesh
Front suspension	Telescopic, coil spring, oil damped
Rear suspension	Link type, coil spring, oil damped, spring preload adjustable
Rake / trail	25°40' / 107 mm
Front brake	Disc, twin
Rear brake	Disc
Front tire size	110/80R19M/C 59V, tubeless
Rear tire size	150/70R17M/C 69V, tubeless
Overall length	2,275 mm
Overall width	910 mm
Overall height	1,405 mm
Wheelbase	1,560 mm
Ground clearance	170 mm
Seat height	835 mm
Curb mass	216 kg
Fuel tank capacity	20.0L
Oil capacity (Overhaul)	3.0L



Dual Spark 90° V-Twin Performance



Analog Tachometer & Digital Speedometer




DC Outlet



Three-way adjustable wind-screen



Wire spoke wheels with tubeless tire



Advanced Traction Control System



Knuckle cover



Engine under cowling

V-Strom 650XT (DL650XA)



Candy Daring Red / Glass Sparkle Black (AV4)



Champion Yellow No.2 (YU1)



* Specifications are subject to change without prior notice
 ** Pictures displayed are for illustration purposes only.
 Actual product may vary.

IMPORTED FROM JAPAN



SUZUKI MALAYSIA SDN. BHD. 202001012115 (1368435-X)

(Sole Importer / Assembler / Distributor for Suzuki Motorcycles, Scooters, ATV, Spare Parts & Accessories)

No.12 & 14, Jalan Jurunilai U1/20, Seksyen U1, Hicom Glenmarie Industrial Park, 40150 Shah Alam, Selangor Darul Ehsan.

Tel: 603-5566 5688 Fax: 603-5566 5699

suzukimalaysia suzukimalaysiasb suzukimalaysia1 www.suzuki.com.my

